

Declaration of performance

DoP number: 12802512-B1W1280

Product name:

TOPAAS

(1) Identification code of product-type is DoP-number

(2) Reference number: 12802512-B1W1280

(4)


Wienerberger

Wienerberger NV
8500 Kortrijk Kapel ter Bede

(3) Intended use(s) in masonry walls, columns and partitions for:

unprotected masonry

(6) Assessment and verification of constancy of performance:

System 2+

(7) Notified Body:

0749

Performed:

(i) initial inspection of the manufacturing plant and of factory production control

(ii) continuous surveillance, assessment and evaluation of factory production control and issued certificate number 0749-CPD-BC2-201

(9) Declared performance:


Type of unit: HD -masonry unit

Dimensions and tolerances

			Tm	Rm
Length:	mm	215	± 6	9
Width:	mm	102	± 4	6
Height:	mm	65	± 3	5
Tolerance:	category	T1		
Range:	category	R1		
Flatness of bed faces:	mm	NPD		
Plane parallelism:	mm	NPD		

Configuration

Group of the unit:	-	1
Volume of all formed voids:	%	NPD
Volume of frogs:	%	< 20



actual configuration may vary slightly

Density

Gross dry density:	kg/m ³	1600
Net dry density:	kg/m ³	1750
Tolerance:	category / %	D1 / 10

Compressive strength

Category:	-	1
Perpendicular to bedface:	N/mm ²	12
Perpendicular to header:	N/mm ²	NPD
Perpendicular to header 2:	N/mm ²	NPD

Bond strength:	N/mm ²	NPD
----------------	-------------------	-----

Thermal conductivity λ_{10} , dry, unit:	W/(m·K)	0.69	Determination method EN 1745:2012: S1
--	---------	------	---------------------------------------

Water vapour permeability:	-	$\mu = 5/10$
----------------------------	---	--------------

Durability:	category	F2
-------------	----------	----

Water absorption:	%	15	EN 772-21
-------------------	---	----	-----------

Initial rate of water absorption:	kg/(m ² ·min)	0.01-6
-----------------------------------	--------------------------	--------

Active soluble salt content:	category	S2
------------------------------	----------	----

Moisture movement:	mm/m	NPD
--------------------	------	-----

Reaction to fire:	class	A1
-------------------	-------	----

Dangerous substances:	-	NPD
-----------------------	---	-----

(10) The performance of the product is in accordance with the specification above.

Signed on behalf of the manufacturer:

CEO

2013-07-01


Johan Van Der Biest

Wienerberger NV
8500 Kortrijk Kapel ter Bede

EN 771-1:2011

Supplementary national information:

DoP number: 12802512-B1W1280

Product name:

TOPAAS

(1) Identification code of product-type is DoP-number

(2) Reference number: 12802512-B1W1280

(4)



Wienerberger NV
8500 Kortrijk Kapel ter Bede